

WOOD/SERIES WS23PTO






270° ADJUSTABLE CHUTE

for better optimization of the orientation on job sites depending on the tractor's position.

POWER TAKE-OFF DRIVEN

For 540 rpm, for tractors up to 80 HP (the power of your tractor will determine the consistency of the No Stress operation).



DOUBLE FEED ROLLER

Son double rouleau ameneur assure un véritable entrainement de la matière pour vous aider au quotidien.

	WS20PTOT
Recommended tractor power	60HP min to 80HP max
	540t/m
Cutting disc diameter (mm)	900
Cutting disc weight (kg)	218
Infeed roller width (mm)	310
Infeed roller diameter (mm)	240
Adjustable chute (°)	270
Hopper dimensions D x W (mm)	1500 x 1290
Hopper loading height (mm)	870
Reference	WS23PTO
Comfort Kit	KITWS23PTO-P

The WS23PTO is also available in PTO turret and diesel turret versions.

The WS23PTO ensures high performance on all your job sites. Chipping branches up to 23 cm with "Cutting Disc" technology, its 270° adjustable chute and two infeed rollers provide working comfort, visibility, and flexibility on every site.

The wide loading hopper makes feeding branches easy and folds for transport, ensuring optimal efficiency. Maintenance and machine monitoring are simplified thanks to its ultra-robust design, conveniently designed service covers, and the Pilot System, which centralizes machine control.

CUTTING DISC

MOTORIZATION
POWER TAKE-OFF

UP TO 23 CM

TS INDUSTRIE CUTTING TECHNOLOGY

The cutting disc of our shredders, also called the Cutting Disc, is a heavy flywheel equipped with two adjustable knives passing in front of a counter blade to make a clean cut of the material, similar to a woodworking planer. This technique produces uniform chips suitable for decorating and mulching plant beds.

